17" LCD MONITOR 1U RACK DRAWER



Model: FR-1502-17

- 17" Slim 1U Rack LCD Monitor
- Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
- Folds down to 1U, 1.75" high
- LCD Stays Open inside a Rack Cabinet
- Field selectable for USB and PS/2
- 17.0" Bright Active Display Area
- Built-in lockable Slide Rails

The model FR-1502-17 is now End-of-Life, if you have a requirement please contact us or see our current lineup of 1U & 2U Rack LCD / Keyboard Drawers.

GALLERY IMAGES





PRODUCT DESCRIPTION

Optimize Rack Space with a Slim 1U LCD Monitor in a Drawer

The 17" LCD Monitor 1U Rack Drawer has been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

The Stealth ultra-thin LCD monitor can operate in its open state even with the rack cabinet doors closed. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available.

Other FlatRack 1U & 2U Rack Drawer models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high Latching front panel w/ 2-point lock
Screen Size	17.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Response Time	1.3ms Typical
Viewable Image Size	Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Built-in Controls for Brightness, Size, Contrast, H-V Position, Frequency, etc.
Environmental	Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-Operating) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Color	Black (standard)
Unit Weight	Unit Weight: 26 lbs (12 Kg)
Available Models	FR-1502-17 – Standard Model
Additional Options	Resistive/Capacitive Touchscreen 12/24/48VDC Power supply HDMI, BNC, S-Video, RCA Inputs

Dimensions	19.0"(W) x 1.75"(H) x 19.7 "(D) (482.6mm x 44.5mm x 500 mm)
Warranty	2 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.