

## 19" WIDESCREEN LCD MONITOR / KEYBOARD 1U RACK DRAWER (DISCONTINUED)



### **Model: FR-1002-19W**

- 19" Slim 1U Rack LCD / Keyboard / Mouse
  - Widescreen 1440 x 900 resolution
  - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
  - Folds down to 1U, 1.75" high
  - Built-in Keyboard & Touch Pad
  - Field selectable for USB and PS/2
- Optional 8, 16 & 32 port KVM, Video Inputs

***(Important Notice: The FR-1002-19W model is now end of life and is replaced by the functional equivalent model FR-1010-19W.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth FlatRack products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a touch pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

**ADDITIONAL INFORMATION**

<b>Construction &amp; Design</b>	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
<b>Screen Size</b>	19.0" (Diagonal)
<b>Type</b>	LCD c/w LED Backlighting
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	1440 x 900 (Auto sync from 720 x 400 to 1440 x 900)
<b>Pixel Pitch</b>	0.283mm x 0.283mm
<b>Response Time</b>	5ms Typical
<b>Viewable Image Size</b>	Horizontal: 16.06" / 408 mm, Vertical: 10.03" / 255 mm
<b>Video Signal</b>	RGB Analog 0.7V Peak to Peak
<b>Video Input Connectors</b>	VGA/HD15 + DVI-D Inputs (standard) HDMI, BNC + S-Video (optional)
<b>Viewing Angle</b>	80 (up), 80 (down), 80 (left), 80 (right)
<b>Contrast Ratio</b>	1000:1 (typical)
<b>Luminance (Brightness)</b>	250 cd/m2 typical at center (250 Nits)
<b>Controls On-Screen Display</b>	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
<b>Input</b>	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 25 Watts, Standby 4 Watts
<b>Built-in Keyboard / Mouse</b>	104 Keys 2 Button Touch Pad USB cable included
<b>Environmental</b>	Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
<b>Color</b>	Black (standard)

Unit Weight	Unit Weight: 25lbs (11.5 Kgs)
Approvals	UL UL (Canada)
Available Models	FR-1002-19W – Standard Model with VGA video connector KVM version with 8 or 16 inputs available KVM (Cat6) version with 8, 16 or 32 inputs available
Additional Options	12/24/48VDC Power supply S-Video + Composite ( BNC ) + Audio input DVI-D or HDMI Input
Dimensions	19.0"(W) x 1.75"(H) x 18.1 "(D) (482.6mm x 44.5mm x 460mm)
Warranty	2 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.