

20" LCD MONITOR / KEYBOARD 1U RACK DRAWER (DISCONTINUED)



Model: FR-1001-20

- 20" Slim 1U Rack LCD / Keyboard / Mouse
 - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
 - Folds down to 1U, 1.75" high
 - Built-in Keyboard & Touch Pad
- Field selectable for USB and PS/2
- 20.0" Bright Active Display Area
 - 1600 x 1200 resolution
 - Built-in lockable Slide Rails
- Optional 8, 16 & 32 port KVM, DC Power, Screen Sizes, Video Inputs

The model FR-1001-20 is now End-of-Life, if you have a requirement please contact us or see our current lineup of 1U & 2U Rack LCD / Keyboard Drawers.



PRODUCT DESCRIPTION

Optimize your Rack Space with a Slim 1U All-In-One LCD/Keyboard in a Drawer

Stealth FlatRack products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

ADDITIONAL INFORMATION**Construction & Design**

19" Rackmount steel chassis
1U , 1.75" or 44.5mm high
Latching front panel w/ 2-point lock

Screen Size

20.0" (Diagonal)

Type

TFT Active Matrix Liquid Crystal

Aspect Ratio

4:3

Native Resolution

1600 x 1200 (Auto sync from 640 x 480 to 1600 x 1200)

Response Time

1ms Typical

Viewable Image Size

Horizontal: 16.06" / 408 mm, Vertical: 12.04" / 306 mm

Video Signal

RGB Analog 0.7V Peak to Peak

Video Input Connectors

VGA / HD15 (Standard)
DVI-D & HDMI (Optional)

Viewing Angle

80 (up), 80 (down), 80 (left), 80 (right)

Contrast Ratio

800:1 (typical)

Luminance (Brightness)

300 cd/m2 typical at center (300 Nits)

Controls On-Screen Display

Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.

Input

Internal 100~240VAC, 50/60Hz Power Supply
Power Consumption: Max. 48 Watts, Standby 5 Watts

Built-in Keyboard / Mouse

104 Keys
2 Button Touch Pad
PS/2 and USB Combo cables included

Environmental

Operating Relative Humidity (non condensing) 20-90%
Storage Relative Humidity (non condensing) 5-90%
Operating Temperature: 0~50C (32~122F)
Storage Temperature: -5~60C (-23~140F)
Shock: 10G acceleration (11ms duration)
Vibration: 5~500Hz 1G RMS random vibration

Color

Black (standard)

Unit Weight

Unit Weight: 44lbs (20.0 Kgs)

Available Models	FR-1001-20 – Standard Model
	KVM version with 8 or 16 inputs available
Additional Options	KVM (Cat6) version with 8, 16 or 32 inputs available
	12/24/48VDC Power supply
	DVI-D, BNC, S-Video, RCA Inputs
Dimensions	19.0"(W) x 1.75"(H) x 25.6"(D) (482.6mm x 44.5mm x 650 mm)
Warranty	2 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.