17" LCD MONITOR / KEYBOARD 1U RACK DRAWER WITH 8 & 16 PORT KVM (FR-1002-17-KVM)



$2,635.00 USD

Model: FR-1002-17-KVM

- KVM with 8 or 16 Ports (DB-15)
- 17" Slim 1U Rack LCD / Keyboard / Mouse
- Control multiple systems from one LCD
- 8/16 Keyboard/Video/Mouse Inputs
- Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
- Folds down to 1U, 1.75" high
- Field selectable for USB and PS/2
- Built-in lockable Slide Rails
- Optional DC Power, Video Inputs
- UL Approved

GALLERY IMAGES







PRODUCT DESCRIPTION

Manage your Rack Space with a Slim 1U All-In-One LCD/Keyboard with 8 or 16 Built-in KVM Ports

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a touch pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION

Construction & Design	19" Rackmount steel chassis 1U , 1.75" or 44.5mm high
Screen Size	17.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.264mm x 0.264mm
Response Time	5ms Typical
Viewable Image Size	Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Video Input Connectors	VGA / HD15 (Standard) DVI-D & HDMI (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Input	Internal 100~240VAC, 50/60Hz Power Supply Power Consumption: Max. 25 Watts, Standby 4 Watts
Built-in Keyboard / Mouse	104 Keys 2 Button Touch Pad PS/2 and USB Combo cables included
Environmental	Operating Relative Humidity (non condensing) 20-90% Storage Relative Humidity (non condensing) 5-90% Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Color	Black (standard)

Unit Weight	Unit Weight: 26 lbs (12 Kg)
Approvals	UL UL (Canada)
Available Models	FR-1002-17-KVM8 – 17" LCD/Keyboard/Touchpad with 8-Port KVM (DB-15) FR-1002-17-KVM16 – 17" LCD/Keyboard/Touchpad with 16-Port KVM (DB-15)
Additional Options	KVM (Cat6) version with 8, 16 or 32 inputs available 12/24/48VDC Power supply S-Video + Composite (BNC) + Audio input DVI-D or HDMI Input
Dimensions	19.0"(W) x 1.75"(H) x 22.8 "(D) (482.6mm x 44.5mm x 579.1 mm)
Warranty	2 Year Parts & Labor