

## 17" LCD MONITOR / KEYBOARD 2U RACK DRAWER WITH 8 & 16 PORT KVM (FR-2002-17-KVM)



**\$2,915.00 USD**

***Model: FR-2002-17-KVM***

- KVM with 8, 12, or 16 Ports (DB-15, or DVI)
- 17" Slim 2U Rack LCD / Keyboard / Mouse
  - Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
  - Folds down to 2U, 3.5" high
  - Built-in Keyboard & Touch Pad
- Field selectable for USB and PS/2
- 17.0" Bright Active Display Area
  - Built-in lockable Slide Rails
- Optional 8, 16 & 32 port KVM, DC Power, Video Inputs



## GALLERY IMAGES



## PRODUCT DESCRIPTION

### **Manage your Rack Space with a Slim 2U All-In-One LCD/Keyboard & Mouse with 8, 12, or 16 Built-in KVM Ports**

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 3.5 inches or 2U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

**ADDITIONAL INFORMATION****Construction & Design**

19" Rackmount steel chassis  
2U , 3.5" or 88.9mm high  
Latching front panel w/ 2-point lock

**Screen Size**

17.0" (Diagonal)

**Type**

TFT Active Matrix Liquid Crystal

**Aspect Ratio**

4:3

**Native Resolution**

1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)

**Response Time**

5ms Typical

**Viewable Image Size**

Horizontal: 13.3" / 337.9 mm, Vertical: 10.6" / 270.4 mm

**Video Signal**

RGB Analog 0.7V Peak to Peak

**Video Input Connectors**

VGA / HD15 (Standard)  
DVI-D (Optional)

**Viewing Angle**

80 (up), 80 (down), 80 (left), 80 (right)

**Contrast Ratio**

1000:1 (typical)

**Luminance (Brightness)**

250 cd/m2 typical at center (250 Nits)

**Controls On-Screen Display**

Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.

**Input**

Internal 100~240VAC, 50/60Hz Power Supply  
Power Consumption: Max. 48 Watts, Standby 5 Watts

**Built-in Keyboard / Mouse**

104 Keys  
3 Button Glide Point  
PS/2 and USB Combo cables included

**Environmental**

Operating Relative Humidity (non condensing) 20-90%  
Operating Temperature: 0~50C (32~122F)  
Storage Temperature: -5~60C (-23~140F)  
Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-Operating)  
Shock: 10G acceleration (11ms duration)  
Vibration: 5~500Hz 1G RMS random vibration

**Color**

Black (standard)

|                    |  |
|--------------------|--|
| Unit Weight        | Unit Weight: 46.4 Lbs (21.1 kg)  |
| Available Models   | FR-2002-17-KVM8 – 17" LCD/Keyboard/Trackpad with 8-Port KVM (DB-15)<br>FR-2002-17-KVM16 – 17" LCD/Keyboard/Trackpad with 16-Port KVM (DB-15) |
| Additional Options | Resistive/Capacitive Touchscreen<br>12/24/48VDC Power supply<br>DVI-D, BNC, S-Video, RCA Inputs  |
| Dimensions         | 19.0"(W) x 3.5"(H) x 18.9"(D) (482.6 x 89.0 x 480 mm)  |
| Warranty           | 2 Year Parts & Labor   |