

8 & 16 PORT USB KVM SWITCH - SK-500 (DISCONTINUED)



Model: SK-500

- KVM Switch with 8 or 16 HD15 Ports
- USB HUB to support Touch Screen Switching
 - Control multiple systems from one point
 - Hot Pluggable, no need to power down
 - Support resolutions up to 1920 x 1200
 - Slim 1U size, 1.75" high
 - Easily Installs into 19" Rack Cabinets
- OS Support: Windows / Linux / Unix / Mac OS
 - Optional 12/24/48/125/250V DC power
 - Optional Remote IP connectivity

The model SK-500 is now end of life, if you still have a requirement please contact us.



GALLERY IMAGES



PRODUCT DESCRIPTION

Manage your Rack Space with 8 or 16 Ports KVM Switch

The Stealth SK-500 USB KVM Switch has a slim 1U form factor to help administrators manage, expand and control your data center that is cost efficient. Control up to 16 PCs from a single Keyboard, Video and Mouse (KVM) console.

To simplify switching and control, the SK-500 models are equipped with an OSD (On-Screen-Display) menu and ability to switch targets via Hot Key sequences. The SK-500 series supports up to 1920 x 1200 resolution and is Hot Pluggable - Add PCs or remove connected PCs for maintenance without powering down the USB KVM switch or PCs.

The KVM Switch measures only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Optional DC Power inputs of 12/24/48/125/250V are configurable for your custom solution. Also available as an option, Remote IP connectivity, easily access your KVM from from any location.

Stealth also provides additional KVM & Cat6 KVM Drawers with a range of LCD sizes, Widescreen, and various video inputs.

ADDITIONAL INFORMATION**KVM Specification**

8 or 16 Ports

Connector: DB-15

Connectivity: Combo 2-in-1 VGA + USB KVM cable, 6 feet

USB Hub: 2 x USB type A for sharing other peripheral devices among the computers

Construction & Design

1U , 1.75" or 44.5mm high

Native Resolution

16:10 Aspect Ratio – Max. 1920 x 1200

4:3 Aspect Ratio – Max. 1600 x 1200

Controls On-Screen Display

Language, Hotkey, Security

Input

Power Consumption: Max. 10W

Operating Temperature: 0~55C (32~131F)

Operating Relative Humidity (non condensing) 20-90%

Storage Relative Humidity (non condensing) 5-90%

Storage Temperature: -20~60C (-4~140F)

Shock: 10G acceleration (11ms duration)

Vibration: 5~500Hz 1G RMS random vibration

Environmental**Color**

Black (standard)

Unit Weight

6.5 lbs / 3 kg

SK-508-VGA-USB-*

SK-508-VGA-USB-IP-*

Available Models

SK-516-VGA-USB-*

SK-516-VGA-USB-IP-*

* Denotes Power options: AC, 12V, 24V, 48V, 125V, and 250V

Optical DC Power Input – 12V (9-18), 24V (18-36), 48V (36-75), 125V (66-160), 250V (180-425)

Additional Options

Remote Networking Connectivity

Dimensions

17.4"(W) x 10.7"(D) x 1.73"(H) / (443 x 271 x 44 mm)

Warranty

2 Year limited Warranty, Standard