

## 15" OPEN-FRAME LCD MONITOR - SV-1510-OEM (DISCONTINUED)




### **Model: SV-1510-OEM**

- 15" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
- Resistive Touch Screen Standard c/w USB and Serial Connections
  - Optional Capacitive Touchscreen
    - Wide Viewing Angles
  - VGA & DVI-D video connectors
    - cULus Listed
  - 1 Year Warranty

***(Important Notice: The SV-1510-OEM model is now end of life and is replaced by the functional equivalent model SV-1505-OEM.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's 15" Open-Frame LCD Monitor is designed to easily install into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place. Our OEM/Open Frame LCD products are available with resistive/capacitive touchscreens or without a front overlay.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Open-Frame
<b>Screen Size</b>	15.0" (Diagonal)
<b>Aspect Ratio</b>	4:3
<b>Native Resolution</b>	1024 x 768 (Auto sync from 640 x 480 to 1024 x 768)
<b>Horizontal Frequency</b>	37.9 kHz ~ 62.4 kHz
<b>Vertical Frequency</b>	48.8 kHz ~ 75.1 Hz
<b>Pixel Pitch</b>	0.297mm x 0.297mm
<b>Response Time</b>	35 ms
<b>Type</b>	LCD c/w LED Backlighting Backlight Life: 50,000 Hrs Typical
<b>Video Input Connectors</b>	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
<b>Viewing Angle</b>	65 (up), 85 (down), 85 (left), 85 (right)
<b>Contrast Ratio</b>	1500:1 (typical)
<b>Luminance (Brightness)</b>	350 cd/m2 typical at center (350 Nits)
<b>Viewable Image Size</b>	Horizontal: 11.97" / 304.1 mm, Vertical: 8.98" / 228.1 mm
<b>Input</b>	90 ~ 264V AC, 47~63Hz External Power Supply (rear mounted) 12V DC Power Jack at LCD
<b>Control Buttons (Rear mounted)</b>	Power Switch, Menu/Select, Exit/Back, Select (+,-), Auto, Hot Brightness (+,-)
<b>Controls On-Screen Display</b>	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
<b>Environmental Rating</b>	OEM/Open-Frame chassis - not rated

## **Environmental**

Operating Temperature: 0 - 40C (32 to 104 F)  
Storage Temperature: 0~60C (32~140F)  
Relative Humidity: 10% ~ 90% non-condensing (Operating & Non-Operating)  
Operating Altitude: 0 to 10,000 ft.  
Storage Altitude: 0 to 40,000 ft.

## **Shock**

30g's, 11ms, ½ Sine

## **Vibration**

1g RMS, 20-500Hz

## **Approvals**

cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07

## **Cooling**

Natural Convection (no fan)

## **Panel Finish**

Black Baked Enamel (Standard)  
Stainless Steel - Brushed #304 (Optional)

## **Unit Weight**

Unit Weight: 7 Lbs (3.2kg) without touchscreen  
Unit Weight: 8 Lbs (3.6kg) with touchscreen

## **Dimensions**

For Dimensions please refer to the OEM Dimensional Drawing

## **Available Models**

SV-1510-OEM: Open Frame unit with AC power input

## **Warranty**

1 Year Parts & Labor  
1 Year Extended Warranty available (see Configurator/Price List)

## **Disclaimer**

Note: Specifications are subject to change without notice.