

15" SUNLIGHT READABLE LCD MONITOR (SV-1505L-OEM-PCT-HB-USB)



\$1,495.00 USD

Model: SV-1505L-OEM-PCT-HB-USB

- 15.0" Sunlight Readable LCD Monitor
- 1,600 Nits (Cd/m2) HIGH BRIGHTNESS
 - LED Backlighting
 - Open-Frame/OEM style enclosure
- Remote Light Sensor for Auto-adjustment of Brightness (standard)
 - Digital controls w/on screen display
- 10-point Multi-Touch (PCT / PCAP) Touchscreen
 - HDMI, DVI-I and DisplayPort Inputs
 - Low Power Consumption
- Panel Mount version also available



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's model SV-1505L-OEM-PCT-HB-USB, 15" Sunlight Readable OEM LCD Display is designed to operate in extreme ambient light with up to 1600 nits brightness. Stealth's high bright monitors outperform commercially available products that wash out in direct and indirect sunlight conditions.

Display brightness can be controlled automatically using the remote light sensor or it can be adjusted manually using the rear mounted OSD. An optional Remote Potentiometer is also available for manual adjustment of the Display brightness. A PCAP Multitouch Capacitive touchscreen is standard. The SV-1505L-OEM-PCT-HB-USB is ideal for installation in marine, mobile, kiosks, control, security, drilling platforms, outdoor displays, aircraft or digital sign applications.

Stealth.com has a wide range of industrial LCD products that include; NEMA 4/4X / IP65 Stainless Steel, Panel Mount, Rackmount, Open Frame and custom designed configurations.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	15.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1024 x 768
Pixel Pitch	0.297mm x 0.297mm
Response Time	23ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	DVI-I HDMI Displayport
Viewing Angle	88°/88°/88°/88° (Typical)
Contrast Ratio	3800:1 (typical)
Luminance (Brightness)	1600 cd/m2 typical at center (1600 Nits)
Viewable Image Size	Horizontal: 11.97" / 304.13 mm, Vertical: 8.98" / 228.10 mm
Input	100-240V AC, 50/60Hz, 60W rear-mounted (removable) Power Supply 12V DC Power Jack at LCD
Control Buttons (Rear mounted)	Power Switch, Menu, +, -
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Environmental Rating	OEM/Open-Frame chassis – not rated
Environmental	Operating Humidity: 20~90%, non-condensing Operating & Storage Temperature: -20 to 70C (-4 to 158 F) Operating Temperature: -20 to 70C (-4 to 158F)
Panel Finish	N/A – Open-Frame
Unit Weight	Add 0.75 Lbs (0.34 Kgs.) for rear-mounted (removable) AC Power Adapter Unit Weight: 9.35 Lbs. (4.24 Kgs.)

Available Models

SV-1505L-OEM-PCT-HB-USB – Multi-Touch (PCT / PCAP)

Touchscreen, USB Interface

SV-1505L-OEM-PCT-HB-POT-USB – includes remote

Potentiometer for brightness adjustment

Dimensions

14.28"(W) x 10.53"(H) x 1.41"(D) (362.7mm x 267.34mm x

35.81mm)

Add 1.49" (38.0mm) to depth with rear mounted AC Adapter

Warranty

1 Year Parts & Labor

Disclaimer

Note: Specifications are subject to change without notice.