

## 19" PANEL MOUNT LCD MONITOR (DISCONTINUED)




### ***Model: SV-1901-PM***

- Panel Mount LCD, 19" Industrial Grade
- NEMA 4/IP65 Environmentally Sealed
- Touch Screen Standard (Capacitive or Resistive)
  - Wide Viewing Angles
- Stainless Steel & Custom painted bezel options
  - 250 Nits of Brightness, Adjustable Controls
  - VGA & DVI-D video connectors
    - cULus Listed
  - 2 Year Warranty

***(Important Notice: The SV-1901-PM model is now end of life and is replaced by the functional equivalent model SV-1905-PM.)***



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth builds high quality LCD monitors suited for industrial and commercial applications. Our 19" Panel Mount LCD Monitor comes equipped with an environmentally sealed front panel that is resistant to splashes or hose downs. All Stealth Panel Mount LCD products are easily installed by securing the rear studs into your console, panel or wall.

Our LCDs are available with various Touch Screen options including Resistive or Capacitive. For non-touch applications our anti-glare protective glass overlay is installed for maximum protection.



Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system and in compliance with being cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07.

We offer Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Stealth's LCD products are environmentally sealed to NEMA 4 / IP65 and are ideal for applications where dirt, dust, moisture and water are present. Stealth's rugged LCD products are constructed from solid steel and stainless steel for corrosion resistance applications.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Panel Mount
<b>Screen Size</b>	19.0" (Diagonal)
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
<b>Horizontal Frequency</b>	30 kHz ~ 83 kHz
<b>Vertical Frequency</b>	56 Hz ~ 75 Hz
<b>Pixel Pitch</b>	0.294mm x 0.294mm
<b>Response Time</b>	5ms Typical
<b>Type</b>	LCD c/w LED Backlighting
<b>Video Input Connectors</b>	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
<b>Viewing Angle</b>	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	1000:1 (typical) SmartContrast: 20,000,000:1
<b>Luminance (Brightness)</b>	250 cd/m2 typical at center (250 Nits)
<b>Viewable Image Size</b>	Horizontal: 14.81" / 376.32 mm, Vertical: 11.85" / 301.06 mm
<b>Input</b>	AC Input: 100-240V, 50-60Hz, 1.5A
<b>Control Buttons (Rear mounted)</b>	Smart Image, Down, Up, Menu/OK, Power ON/OFF
<b>Controls On-Screen Display</b>	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
<b>Environmental Rating</b>	Standard Bezel: NEMA 4 / IP65 Front Panel (when properly installed) protection against windblown dust and rain, splashing water, and hose-directed water Optional Stainless Steel Bezel: NEMA 4X / IP65 Front Panel (when properly installed) corrosion protection, protection against windblown dust and rain, splashing water, and hose-directed water

## Environmental

Operating Temperature: 0 - 40C (32 to 104 F)

Storage Temperature: -20~60C (-4~140F)

Operating: Relative Humidity 20% ~ 80%

Storage Relative Humidity: 20% ~ 80%

## Approvals

cULus Listed, UL 60950-1 & CAN/CSA C22.2 No. 60950-1-07

## Panel Finish

Black Baked Enamel (Standard)

Stainless Steel - Brushed #304 (Optional)

## Unit Weight

Unit Weight: 17.3 Lbs (7.86 Kg)\*

Shipping Weight: 23.85 Lbs (10.82 Kg)\*

\* Weight may vary depending on configuration

## Dimensions

Panel Mount: 21.0"(W) x 17.5"(H) x 2.56"(D) 533.4mm x 444.5mm x 65mm

## Available Models

SV-1901-PM-RT - Standard Bezel (NEMA 4), Resistive Touch with USB & Serial/DB9 Interfaces

SV-1901-PM-CT-SERIAL - Standard Bezel (NEMA 4), Capacitive Touch with Serial/DB9 Interface

SV-1901-PM-CT-USB - Standard Bezel (NEMA 4), Capacitive Touch Screen with USB & Serial/DB9 Interfaces

SV-1901-PM-RT-SS - Stainless Steel Bezel (NEMA 4X), Resistive Touch with USB & Serial/DB9 Interfaces

SV-1901-PM-CT-SS-SERIAL - Stainless Steel Bezel (NEMA 4X), Capacitive Touch with Serial/DB9 Interface

SV-1901-PM-CT-SS-USB - Stainless Steel Bezel (NEMA 4X), Capacitive Touch Screen with USB & Serial/DB9 Interfaces

## Warranty

2 Year Parts & Labor

1 Year Extended Warranty available (see Configurator/Price List)

## Disclaimer

Note: Specifications are subject to change without notice.