

## 21.5" RACK MOUNT LCD MONITOR (SV-2155W-RM)



**\$1,655.00 USD**

***Model: SV-2155W-RM***

- 21.5" Wide Screen Rack Mount LCD
- Full 1080p HD resolution (1920 x 1080)
- VGA and HDMI Inputs (Optional DVI-D & Displayport)
  - Installs into (8U) of rack space
  - Easy snap in/out installation
- Optional Resistive Touch Screen
  - Front-access OSD Controls
  - 2 Year Warranty



## GALLERY IMAGES



## PRODUCT DESCRIPTION

The Stealth model SV-2155W-RM is our widescreen 21.5" Rack Mount LCD which installs into industry standard 19" EIA rack cabinets and enclosures in minutes. The SV-2155W-RM features a Full HD 1080p display (1920 x 1080 resolution), 16:9 Aspect Ratio with VGA and HDMI video inputs standard. Optional upgrades are available for VGA, DVI-D & HDMI or VGA, DisplayPort and dual HDMI video connections.

Both options include integrated Audio and dual 2 Watt Speakers. The 21.5" Rack display can also be configured with a Resistive Touch Screen and DC power options including 12V, 24V, 48V, 125V and 250V DC.

Stealth builds high quality Rackmount LCD monitors suited for industrial and commercial applications. We offer a wide range of LCD product offerings including Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

**ADDITIONAL INFORMATION**

<b>Bezel Type</b>	Rack Mount
<b>Screen Size</b>	21.5" (Diagonal)
<b>Aspect Ratio</b>	16:9
<b>Native Resolution</b>	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
<b>Pixel Pitch</b>	0.248mm x 0.248mm
<b>Response Time</b>	5ms Typical
<b>Type</b>	LCD c/w LED Backlighting
<b>Video Input Connectors</b>	VGA/HD15 + DVI-D + HDMI inputs with Audio In/Out, Dual 2W Speakers (optional) VGA/HD15 + HDMI Inputs (standard) VGA/HD15 + 2x HDMI + DisplayPort with Audio In/Out, Dual 2W Speakers (optional)
<b>Viewing Angle</b>	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	1000:1 (typical)
<b>Luminance (Brightness)</b>	250 cd/m2 typical at center (250 Nits)
<b>Viewable Image Size</b>	Horizontal: 18.77" / 476.64mm, Vertical: 10.56" / 268.11mm
<b>Input</b>	Optional: 12V, 24V, 48V, 125V and 250V DC with Terminal Block Power Consumption: 32W Max, Standby 4W 12VDC input at LCD, Rear mounted AC power supply included, AC Input: 100-240VAC 60/50 Hz @ 0.7A
<b>Audio</b>	Includes: 2 x 2W Speakers with 3.5mm Audio Jack Available only with DV4 and DP Options
<b>Control Buttons (Rear mounted)</b>	Smart Image, Down, Up, Menu/OK, Power ON/OFF
<b>Controls On-Screen Display</b>	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
<b>Environmental Rating</b>	N/A - not rated

## Environmental

Non-Operating Altitude: 40,000 ft  
Operating Altitude: 16,000 ft  
Operating Humidity: 20~90%, non-condensing  
Storage Humidity: 5~90%, non-condensing  
Vibration: 10-300Hz 0.5G RMS random vibration  
Operating Temperature: 0~55C (32~131F)  
Storage Temperature: -20~60C (-4~140F)  
Shock: 10G acceleration (11ms duration)

## Panel Finish

Black Front Panel Finish

## Unit Weight

Unit Weight: 19.4lbs / 8.8 kg

## LCD Mounting Options

Rear VESA 100mm Mounting  
Installs into (8U) of rack space  
Designed to fit standard 19" EIA Racks

## Dimensions

Rack Mount: 19.75"(W) x 13.89"(H) x 2.53"(D) (501.9mm x 353mm x 64.4mm)  
SV-2155W-RM – Standard Model with VGA/HD15 and HDMI 1.4 inputs  
SV-2155W-RM-DP – incl. VGA/HD15, HDMI 1.4, HDMI 2.0, DisplayPort 1.0 with Audio In/Out, Dual 2W Speakers  
SV-2155W-RM-DV4 – incl. VGA/HD15, DVI-D, HDMI 1.4 with Audio In/Out, Dual 2W Speakers

## Available Models

SV-2155W-RM Options:  
-RTe-USB (Resistive Touchscreen with USB interface)  
-12V (9~18VDC input)  
-24V (18~36VDC input)  
-48V (36~75VDC input)  
-125V (66~160VDC input)  
-250V (180~425VDC input)

## Warranty

2 Year Parts & Labor

## Disclaimer

Note: Specifications are subject to change without notice.