

21.5" RACK MOUNT LCD MONITOR (DISCONTINUED)




Model: SV-2150W-RM

- 21.5" Wide Screen Rack Mount LCD
- Full 1080p HD resolution (1920 x 1080)
 - VGA, DVI-D and HDMI Inputs
- Installs into (8U) of rack space
- Easy snap in/out installation
 - Touch Screen Options
 - PIP & Picture by Picture
 - Built-in audio speakers
- Front-access OSD Controls
 - 2 Year Warranty

(Important Notice: The SV-2150W-RM model is now end of life and is replaced by the functional equivalent model SV-2155W-RM.)



GALLERY IMAGES



PRODUCT DESCRIPTION

The Stealth model SV-2150W-RM is our widescreen 21.5" Rack Mount LCD which installs onto industry standard 19" EIA rack cabinets and enclosures in minutes. The SV-2150W-RM also features a Full HD 1080p display (1920 x 1080 resolution), 16:9 Aspect Ratio and supports PIP & Picture by Picture capability with VGA, DVI-D and HDMI inputs. The 21.5" Rack display is also available with either Resistive or Capacitive Touch Screen options.

Stealth builds high quality Rackmount LCD monitors suited for industrial and commercial applications. We offer a wide range of LCD product offerings including Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

ADDITIONAL INFORMATION

Bezel Type	Rack Mount
Screen Size	21.5" (Diagonal)
Aspect Ratio	16:9
Native Resolution	1920 x 1080 (Auto sync from 640 x 480 to 1920 x 1080)
Pixel Pitch	0.248mm x 0.248mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 14.81" / 376.32 mm, Vertical: 11.85" / 301.06 mm
Input	12VDC input at LCD, Rear mounted AC power supply included, AC Input: 100-240VAC 60/50 Hz @ 0.7A Power Consumption: Max. 48 Watts, Standby 5 Watts 2 x 2W Power
Audio	Standard Model Sound via HDMI only Optional 3.5mm audio jacks for audio in & out
Control Buttons (Rear mounted)	Smart Image, Down, Up, Menu/OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental Rating	N/A - not rated

Environmental	Operating Temperature: 0~50C (32~122F) Storage Temperature: -5~60C (-23~140F) Relative Humidity: 5% ~ 90%, non-condensing (Operating & Non-Operating) Shock: 10G acceleration (11ms duration) Vibration: 5~500Hz 1G RMS random vibration
Panel Finish	Black Front Panel Finish
Unit Weight	Unit Weight: 22 Pounds (10Kg)
LCD Mounting Options	Installs into (8U) of rack space Designed to fit standard 19" EIA Racks
Dimensions	Rack Mount: 19.75"(W) x 13.89"(H) x 2.53"(D) (501.9mm x 353mm x 64.4mm)
Available Models	SV-2150W-RM - Standard Model SV-2150W-RM-RT-USB - Resistive Touch Screen with USB Interface SV-2150W-RM-CT-USB - Capacitive Touch Screen with USB interface
Additional Options	S-Video + Composite (BNC) + Audio input Internal 48V, 24V or 12VDC power with DC Terminal Block MIL-type or lockable connectors 3G / HD / SD-SDI Broadcast-grade input Multi-touch
Warranty	2 Year Parts & Labor
Disclaimer	Note: Specifications are subject to change without notice.