

## 17" RUGGED DESKTOP INDUSTRIAL LCD MONITOR (TT-1705)




### ***Model: TT-1705***

- 17" Rugged Metal Enclosed Industrial LCD Monitor
  - Resistive Touch Screen Standard
  - Supports VESA 100mm Mounting
    - 17.0" Active Display Area
  - Wide range DC input (9 - 36V DC)
  - Wide Operating Temp (-10C - +60C)
- Ideal for use in industrial and commercial environments
  - 3 Year Warranty

**If you have a requirement please contact us  
for availability of this model.**



## GALLERY IMAGES



## PRODUCT DESCRIPTION

Stealth's TT-1705 is a 17" Rugged Touch Screen Industrial LCD Monitor designed to deliver performance and reliability that is ideally suited for industrial and commercial environments.

This Industrial LCD Display is available with resistive or capacitive touch screen options and includes support for wide range DC input (9 - 36V DC) and extended operating temperature of -10C - +60C (14F - 140F).

The TT-1705 comes standard with a 3 Years Warranty and also features rear VESA 100mm mounting allowing it to be connected to a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

In addition to our Rugged Desktop Displays, Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes.

**ADDITIONAL INFORMATION**

<b>Screen Size</b>	17.0" (Diagonal)
<b>Aspect Ratio</b>	5:4
<b>Native Resolution</b>	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
<b>Pixel Pitch</b>	0.264mm x 0.264mm
<b>Response Time</b>	30ms (Typical)
<b>Type</b>	TFT Active Matrix Liquid Crystal
<b>Video Input Connectors</b>	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI
<b>Viewing Angle</b>	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
<b>Contrast Ratio</b>	800:1 (typical)
<b>Luminance (Brightness)</b>	350 cd/m2 typical at center (350 Nits)
<b>Viewable Image Size</b>	Horizontal: 13.3" / 337.92 mm, Vertical: 10.6" / 270.34 mm
<b>Input</b>	DC Input: 9V - 36V DC AC Adapter is Removable AC Input: 100-240V, 50-60Hz, 1.5A
<b>Control Buttons (Rear mounted)</b>	Power, Left, Right, Menu
<b>Controls On-Screen Display</b>	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
<b>LCD Mounting Options</b>	Rear VESA 100mm Mounting
<b>Environmental</b>	Operating Temperature: -10C - +60C (14F - 140F) Storage Temperature: -30C - +85C (-22F - +185F) Operating: Relative Humidity 20% ~ 80% Storage Relative Humidity: 20% ~ 80%
<b>Panel Finish</b>	Black Powder Coated
<b>Unit Weight</b>	Shipping Weight: 18.0 Lbs (8.17Kg) Unit Weight: 12.5 Lbs (5.7Kg)

**Dimensions**

16.52" x 13.48" x 4.45" (419.73mm x 342.51mm x 112.95mm)  
Without Mounted AC Adapter: 16.52" x 13.48" x 3.04"  
(419.73mm x 342.51mm x 77.22mm)

**Available Models**

TT-1705-RT - Resistive (USB and Serial/DB9)

**Warranty**

3 Year Parts and Labor

**Disclaimer**

Note: Specifications are subject to change without notice.