

19" SUNLIGHT READABLE OPEN-FRAME LCD MONITOR (DISCONTINUED)



Model: SV-1900LED-OEM-HB

- 19.0" Sunlight Readable OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
 - 1,000 Nits (Cd/m2) HIGH BRIGHTNESS
 - LED Backlighting
 - Adjustable Brightness Controls
 - Touchscreen Optional (Resistive or Capacitive)
 - High Shock & Vibration
 - Low Power Consumption
 - Remote Brightness Control Option
 - Digital controls w/on screen display
 - Also available in Panelmount Design

Important Notice: The SV-1900LED-PM-OEM model is now end of life, please contact us if you have a requirement.



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth.com's 19" Sunlight Readable Open-Frame LCD Monitor is designed to operate in extreme ambient light conditions. Stealth high bright monitors outperform commercially available products that wash out in direct and indirect sunlight conditions.

This 19" Sunlight Readable Open-Frame Display is rated for 1,000 Nits (Cd/m²) high brightness and comes equipped with adjustable brightness controls. The display can also be configured with Resistive or Capacitive touchscreen. Ideal for inside and outside use in marine, mobile, kiosks, control, security, drilling platforms, outdoor displays, yachts, aircraft or digital sign applications.

Stealth.com has a wide range of industrial LCD products that include; NEMA 4/4X / IP65 Stainless Steel, Panel Mount, Rackmount, Open Frame and custom designed configurations.

ADDITIONAL INFORMATION

Bezel Type	Open-Frame
Screen Size	19.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.294mm x 0.294mm
Response Time	5ms Typical
Type	LCD c/w LED Backlighting
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right) – (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	1000 cd/m2 typical at center (1000 Nits)
Viewable Image Size	Horizontal: 14.82" / 376.32 mm, Vertical: 11.85" / 301.06 mm
Video Signal	RGB Analog 0.7V Peak to Peak
Sync Signal	LVDS
Input	Universal Power Supply (removable) 90-240V, +12VDC@37W Power Consumption: 37 W (typical)
Control Buttons (Rear mounted)	Power Switch, Menu Key, Select (+, -), Auto
Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Environmental Rating	OEM/Open-Frame chassis – not rated
Panel Finish	Stainless Steel – Brushed #304 (Standard)
Unit Weight	Unit Weight: 19 Lbs (8.65Kg)

Available Models

SV-1900LED-OEM-RT-HB-SERIAL – Resistive Touch with Serial/DB9 Interface

SV-1900LED-OEM-RT-HB-USB – Resistive Touch with USB Interface

SV-1900LED-OEM-CT-HB-SERIAL – Capacitive Touch with Serial/DB9 Interface

SV-1900LED-OEM-CT-HB-USB – Capacitive Touch with USB Interface

Dimensions

For Dimensions please refer to the OEM Dimensional Drawing

Warranty

1 Year Parts & Labor

Disclaimer

Note: Specifications are subject to change without notice.