

# LPC-460FM Fanless Vehicle/Mobile Mini PC

A full featured fanless mini PC ideal for mobile & DC powered applications

### So Small - So Powerful - So Mobile

The Stealth Computer model LPC-460FM is a highly reliable, fanless, energy efficient, rugged mini PC designed for mobile applications such as Police, Fire, Emergency, Public Service, Taxi, Aeronautics, Vehicle Entertainment and Marine Navigation to name a few.



Stealth's model LPC-460FM PC operates within a wide range of DC input power, 10-26VDC and is equipped with a lockable connector to avoid power interruptions. The robust extruded aluminum chassis performs as a passive heat sink that dissipates internal heat buildup and provides for noise free continuous operation. There are no internal fans that can suck in dust or other contaminates leading to potential catastrophic failures.

Stealth.Com is an ISO 9001 recognized industry leader in the development of small form factor and specialized computers for industrial and commercial markets. For unsurpassed performance and reliability contact Stealth today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584) or International 905-264-9000.

# Model: LPC-460FM - Fanless Mobile Mini PC with DC Input







## **Features:**

- Start Up / Shut Down Delay Feature
- DC Power Input 10V-26VDC
- Fanless, Noise Free, no dust sucking
- Ideal for mobile/field Use
- Small Size for Easy Deployment
- Powerful Intel Mobile Processors
- Intel Graphics Media Accelerator 4500MHD
- 3D Graphics with 16x9 Capability
- Built-in Gigabit LAN, USB 2.0, 1394a Firewire, Audio, Serial, Video
- Rugged Aluminum Chassis
- Solid State Hard Drives (SSD) optional
- Windows 7 & XP Pro Compatible,
   \*other O/S Options Available
- See our FAQ Why Choose Fanless?
- Dimensions:

6.1"(W) x 10.0"(D) x 2.17"(H) (15.9 x 25.0 x 5.5 cm)

## **LPC-460FM Specifications**

#### Processor

- Intel T3100 Celeron Dual-Core processor,
- 1.9GHz Clock Speed, 64-Bit support
- 800 MHz FSB, 1MB L2 Cache





### Chipset

- Intel's GM45 Chipset with Intel's ICH9M
- Integrated IEEE 1394a LSI L-FW3227-100 6-Pin Firewire chipset (supports 400Mb transfer rates)
- Winbond W83627EHG

#### BIOS

- Award PnP Flash BIOS

#### Memory

- 2 DDR2 SO-Dimm memory slots providing options from 4GB (Standard offering) to 8GB's (MAX) of RAM

#### • Internal Storage

- Offered with 500 GB Serial ATA (SATA) with options of up to 1TB
- Optional Solid State Disk Drive (SSD) Serial ATA

### Optical Drives

- Slim Slot Loading DVD-RW / CD-RW (Serial-ATA)
- Optional DVD-RW / Blu-Ray\* Burner Serial ATA (SATA)
- \*NOTE: Blu-Ray playback is not supported on Windows XP

#### • Video (Video Resolutions Supported)

- Onboard Intel Graphics Media Accelerator 4500MHD
- Shared 128MB Video Memory with DVMT
- Includes VGA / HD-15 port and DVI-D (digital Only)
- Dual Display supported (clone or extended desktop)

## Ethernet Port

- Integrated 10/100/1000 Base-T Intel Pro 1000 PL (82573L) Gigabit Ethernet controller, RJ45 connection (PXE support)

#### Audio

- Integrated Realtek High Definition Audio CODEC ALC888

## Mobile PC Features

- Hardware startup Delay 8secs (approx)
- Hardware shutdown delay, instant
- Mobile Wiring Drawing

### Operating Systems

- Supports Windows XP (32-Bit and 64-Bit\*), Windows 7 (32-Bit and 64-Bit\*), Server 2008 (32-Bit and 64-Bit\*), Ubuntu LINUX and more

- Optional: QNX & embedded.

- Contact us for your specific operating system requirement to discuss compatibility

### Power Input

Rear Locking 4-Pin power Jack ideal for mobile applications

- Input is 10V 26VDC (84W MAX)
- Includes Power Input Cable with stripped ends
- No External AC Adapter included (optional AC supply available)



#### • Power Consumption

Power off state: (1.29W)\*
Initial Start-up / Power Up Peek: (45W)\*
Windows Idle: (14W)\*
Full Load: (39W)\*
\*Based on T3100 CPU, 160GB HDD
and 4GB RAM under Windows XP

#### Included with System

- Locking DC Power cord with bare ends
- Wiring Diagram
- 4 Rubber Feet
- DVD Playback Software

(Cyberlink\*, Included only when Windows 7 not purchased)

- CD Burning Software (Nero\*, subject to change)

\*NOTE: Subject to change without notice

#### Options

- Solid State Drives (SSD) SATA
- Wall Mount Bracket
- Remote power option Ideal for OEM or Cabinet manufacturers
- Mobile Bench Test Kit (for use with AC power)

#### Rear Panel (Click here for layout)

- 2 x RS232 COM port
- 2 PS/2 ports for Keyboard & Mouse
- Gigabit RJ45 Network connection
- Audio Line-Out Jack
- 2 x USB 2.0 Ports
- Analog VGA / HD-15 and DVI-D (Digital only) Output (Supports Dual Display)
- Locking 4-Pin DC Power Input Jack

## • Front Panel (Click here for layout)

- IEEE 1394a Firewire port (Powered interface)
- 1 x USB 2.0 Port
- Microphone Input Jack
- Headphone output Jack
- Power-on button
- Reset button
- Power and Hard Drive notification LED

#### Dimensions

- 6.1"(W) x 10.0"(D) x 2.17"(H) (15.9 x 25.0 x 5.5 cm)

- Fanless Chassis sectional drawing (PDF)

#### Environmental

- Operating Temperature: 0-40C
- Non-Operating Temperature: (Storage) -20~60C
- Operating RH (non condensing) 10-80%
- Non Operating RH (non condensing) 0-90%

## Shipping Weight

- Shipping Weight: 6.5 Lbs / 2.9 KG (Depending on configuration)

\*Note: 64-Bit Support is dependant on using a 64-Bit

Supported CPU





- Unit Weight: 3.45 lbs / 1.56 KG (Depending on configuration)
- Power supply Weigh: 1.35 lbs / 0.62 KG

## Warranty

- 1 Year limited Warranty, Standard Extended Warranty available, contact Stealth for more

#### **Power Management** - ACPI 1.0b compliant and Operating System

direct power management

- Wake-on event (Real Time Clock / RTC, USB Keyboard, LAN / Network, Keyboard, Mouse)

#### **Hardware Monitor**

- Processor temperature
- Cooling fan speed
- Voltage

## **Chassis Description**

- Low Profile Rugged Aluminum Chassis

Note: Specifications are subject to change without notice. All other trademarks and copyrights are the property of their respective owners.