



Features:

- 12.1" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
- Touch Screen Options (Resistive)
- 250 Nits of Brightness, Adjustable Controls
- Also available in Panelmount and Rackmount Designs

SV-1200-OEM - Pricelist

12" OEM/Open-Frame LCD Monitor

Stealth's 12.1" Open Frame/OEM LCD design easily installs into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place.

Our Open Frame LCD products are offered with an environmentally sealed NEMA 4, 4X, 12, IP52, IP56 front panel that is resistant to dust/dirt penetration or even liquid splashes. They are available with resistive/capacitive touchscreens, protective anti-glare, Anti-Reflective protective glass or without a front overlay whatsoever.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 6.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

Stealth is an ISO 9001 manufacturer with two decades of proven success at delivering high quality product solutions and excellent support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584).

SV-1200-OEM Specifications

Screen Size	12.1" (Diagonal)
-------------	------------------

Aspect Ratio	4:3
Native Resolution	800 x 600 (Auto sync from 640 x 480 to 800 x 600)
Horizontal Frequency	31 kHz ~ 48 kHz
Vertical Frequency	60 Hz ~ 75 Hz
Pixel Pitch	0.30mm x 0.30mm
Response Time	30ms Typical
Type	TFT Active Matrix Liquid Crystal
Video Input	Display Signal 15 Pin Mini D-Sub DUAL Input Optional: NTSC, PAL, S-VIDEO
Viewing Angle	10 (up), 20 (down), 40 (left), 40 (right) - (<i>Viewing angle of LCD panel sans touch/AR glass</i>)
Contrast Ratio	150:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 9.68" / 246 mm Vertical: 7.26" / 184.5 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms Optional NTSC, S-Video, PAL
Sync Signal	Separate Sync, Composite Sync, Sync on Green, (Positive/Negative)
Operating Temperature	0 - 40C (32 to 104 F) Humidity 30% ~ 80%, non-condensing Altitude Sea Level to 12,000 ft
Storage Temperature	-10 - 60C (-14 to 140 F) Humidity 10% to 90%, non-condensing Altitude Sea Level to 53,000 ft.
Input	AC Input: 110-240VAC 50/60Hz DC Power Adapter (removable) 12VDC Input 2.9A
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM

Lockout, OSM Time-out

Environmental	OEM/Open-Frame chassis - not rated
Panel Finish	N/A - Open-Frame
Unit Weight	Unit 8.4 lbs (3.8 Kgs)

Available Open Frame (OEM) Models:

SV-1200-OEM

- *No protective glass, LCD directly exposed*

SV-1200-OEM-AR

- *Protective Anti-Reflective Glass*

SV-1200-OEM-RT-SERIAL

- *Resistive Touch with Serial/DB9 and USB Interface*

Additional Options

- ODM/OEM to meet exact needs, call to discuss your needs

- Removable Computer Module on LCD Monitor

Product Bundle	Bundle with a Stealth LittlePC or Panelmount Computer and Save - <i>see pricelist links above for more details</i>
----------------	---

Warranty

1 Year Parts & Labor

NOTE: Specifications subject to change without notice.