



Front View



Rear View



Side View



Connectors



Video Cables

15.0" Non Industrial, Light-Rugged LCD

- Touch Screen or Protective Glass Shield
- DVI-I, VGA, PAL, S-Video, NTSC Composite Inputs
- 15.0" TFT LCD w/ Wide Viewing
- Versatile VESA Mounting Options
- 12VDC Input, Ideal for Mobile
- Custom OEM Designs Available

15" Light Rugged LCD Monitor

Stealth's Light Rugged LCD is excellent for applications where a true Industrial Rugged LCD is not required. Our Non Industrial, Light Rugged LCD products offer features that are not available in a standard commercial grade desktop LCD. Resistive/Capacitive touch-screens or an anti-reflective protective glass overlay are standard offerings. Stealth.com light rugged LCD's ship with multiple video inputs including; DVI-I, VGA, S-Video, PAL and NTSC at no additional cost. The 12VDC input and versatile mounting allow for easy installation into mobile, remote or fix mounted applications.

Contact us today to discuss your application with one of our product specialists. Toll Free USA/Canada: 1-888-STEALTH (1-888-783-2584) or International, 905-264-9000.

SV-1500-DT Specifications

Screen Size	15.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal Display (LCD)

Aspect Ratio	4:3
Native Resolution	XGA 1024 x 768 (Auto sync from 640 x 480 to 1024 x 768)
Video Mode	Supports PIP (Picture in Picture)
Input Mode	Supports NTSC or PAL NTSC 525lines, 60 fields PAL 325 lines, 50/60 fields
Display Colors	16M Colors
Horizontal Frequency	31.47 KHz – 68.7 KHz
Vertical Frequency	60 Hz - 85 Hz
Pixel Pitch	0.297mm x 0.297mm
Response Time	15ms (Rise time), 10ms (Decay time) typical
Backlight	2 CCFL backlight bulbs
Video Input	<ul style="list-style-type: none"> - DVI-I Connector on rear, supplied with DVI to VGA/DVI cable (able to connect either using one cable) - RGB Analog input, Video Analog RGB 0.7Vp-p/75 Ohm, Separate Sync - S-Video input - AV Input (RCA) for Video and Audio - DDC 1/2B compliant
Viewing Angle	75 (up), 75 (down), 75 (left), 75 (right) (optional touch screen or Anti Reflective (AR) glass will reduce viewing)
Contrast Ratio	500:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Audio Input	Stereo input jack, comes with 2 internal speakers, 2Watts
Operating Temperature	0 - 40C (32 to 103 F) Humidity 10% ~ 85%, non-condensing
Storage Temperature	-20 - 60C (-4 to 140 F) Humidity 10% to 95%, non-condensing
Input	12VDC input at LCD, Supplied AC power adapter included, 110 – 240V AC (Auto-sensing), 48-62Hz Power Consumption: 50W maximum, 2W power

saving mode

Backlighting Life	50,000 Hr @ 25C
Control Buttons	Front mounted - On/Off - Menu Controls: Auto-Adjustment, Contrast, Brightness, Phase and Color Temperature
On Screen Display	Brightness, Contrast, Hue, Saturation, Auto Color, Color Temperature, User Color, Auto Configuration, Phase, Clock, Display Horizontal Position, Display Vertical Position, PIP, PIP Color Control, Volume, Mute, Source, OSD Configuration Factory Preset, OSD Timer, OSD Horizontal Position, OSD Vertical Position, OSD Transparency
Weight	16.5lbs (7.5 Kgs)
Enclosure Type	Plastic encapsulated -Black color (standard) -White (optional)
Agency Approvals	FCC-B, CE, UL, TUV, MPR-II
Available Models:	SV-1500-DT - <i>Standard Model</i> SV-1500-DT-AR - <i>Protective Anti-Reflective Glass</i> SV-1500-DT-RT - <i>Resistive Touch with Serial/DB9 Interface</i> SV-1500T-DT-RT-USB - <i>Resistive Touch with USB Interface</i> SV-1500-DT-CT - <i>Capacitive Touch Screen with Serial/DB9 interface</i> SV-1500-DT-CT-USB - <i>Capacitive Touch Screen with USB interface</i>
Dimensions	114.88"(W) x 13.78"(H) x 5.98"(D) 378mm x 350mm x 152mm
Included Accessories	DVI to VGA/DVI video cable, AC to DC Power adapter, North American power cord, Audio Cable, Mini Din and RCA cable, Serial Cable (as needed for touch option), USB Cable (as needed for touch option), Driver CD (as needed for touch option only)
Additional Options	

- VESA Plate (used to mount display on VESA compliant arms)
- 3" Wall Mount (Used to mount display on a wall with 3" spacing from wall to LCD display)
- 6" Wall Mount (Used to mount display on a wall with 6" spacing from wall to LCD display)

Product Bundle	Bundle with a Stealth LittlePC or Panelmount Computer and Save <i>- see pricelist links above for more details</i>
----------------	---

Warranty 1 Year Parts & Labor

NOTE: Specifications subject to change without notice.