



**Features:**

- 15" OEM/Open-Frame LCD Monitor
- Easily installs in kiosks, cabinets, walls, panels & consoles
- Touch Screen Options (Resistive or Capacitive)
- Wide Viewing Angles
- 300 Nits of Brightness, Adjustable Controls
- Also available in Panelmount and Rackmount Designs

**SV-1500T-OEM - Pricelist**

## 15" OEM/Open-Frame LCD Monitor

Stealth's 15" Open Frame/OEM LCD design easily installs into your enclosure, cabinet, console, wall, kiosks or other applications. Mounting is straightforward with solid steel metal flanges located on all sides of the LCD each with mounting holes to secure the LCD in place.

Our Open Frame LCD products are offered with an environmentally sealed NEMA 4, 4X, 12, IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. They are available with resistive/capacitive touchscreens, protective anti-glare, Anti-Reflective protective glass or without a front overlay whatsoever.

Stealth offers a wide range of LCD product offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 6.4" up to 24" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

Stealth is an ISO 9001 manufacturer with two decades of proven success at delivering high quality product solutions and excellent support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584).

### SV-1500T-OEM Specifications

Screen Size	15.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1024 x 768 (Auto sync from 640 x 480 to 1024 x 768)
Horizontal Frequency	31.5 kHz - 60 kHz
Vertical Frequency	56 Hz - 76 Hz
Pixel Pitch	0.297mm x 0.297mm
Response Time	2ms (Rise time), 6ms (Decay time) typical
Backlight	2 CCFL backlight bulbs
Video Input Connectors	Analog (VGA / HD-15), DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	65 (up), 75 (down), 70 (left), 70 (right) - <i>(Viewing angle of LCD panel sans touch/AR glass)</i>
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Operating Temperature	0 - 45C (32 to 113 F) Humidity 20% ~ 85%, non-condensing
Storage Temperature	-20 - 60C (-4 to 140 F) Humidity 10% to 90%, non-condensing
Input	12VDC input at LCD, Rear mounted AC power supply included, 100 – 240VAC Power Consumption: <25W (typical)
Backlighting Life	50,000 Hr @ 25C
Control Buttons	Rear mounted
Environmental	OEM/Open-Frame chassis - not rated
Panel Finish	N/A - Open-Frame

**SV-1500T-OEM**

- *No protective glass, LCD directly exposed*

**SV-1500T-OEM-AR**

- *Protective Anti-Reflective Glass*

**SV-1500T-OEM-RT**

- *Resistive Touch with Serial/DB9 and USB Interface*

**SV-1500T-OEM-CT-SERIAL**

Available Open Frame (OEM) Models:

- *Capacitive Touch with Serial/DB9 Interface*

**SV-1500T-OEM-CT-USB**

- *Capacitive Touch Screen with USB interface*

Additional Options

- ODM/OEM to meet exact needs, call to discuss your needs

- Removable Computer Module on LCD Monitor

Product Bundle

Bundle with a Stealth LittlePC or Panelmount Computer and Save

- *see pricelist links above for more details*

Warranty

1 Year Parts & Labor

*NOTE: Specifications subject to change without notice.*