

Features:

- Rack Mount LCD, 15" Industrial Grade
- Installs in standard 19" rack cabinets
- Resistive Touch Screen Standard c/w USB and Serial Connections
- NEMA 4 / IP65 Environmentally Sealed
- 250 Nits of Brightness
- Optional Capacitive Touchscreen
- 2 Year Warranty
- Also available in Panelmount and OEM/Open-Frame Designs




Front View



Rear View



Side View



Rear Controls/
Connectors

15" Rack Mount LCD Monitor

Stealth builds high quality LCD monitors suited for industrial and commercial applications. Our 15" Rack Mount LCD is easily installed into industry standard 19" EIA rack cabinets and enclosures in minutes. Our rack mountable LCD products are built with an environmentally sealed NEMA 4 / IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. The SV-1500T2-RM panel mount lcd comes equipped with Resistive Touch Screen standard and Capacitive touch screen is also available as an option.

Stealth offers a range of LCD product offerings including Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 6.5" up to 26" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

An ISO 9001 manufacturer with over two decades of proven success, Stealth has built a reputation for delivering quality solutions and support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584).

SV-1500T2-RM Specifications

Screen Size	15.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1024 x 768 (Auto sync from 640 x 480 to 1024 x 768)
Horizontal Frequency	31.5 kHz - 60 kHz
Vertical Frequency	60 Hz - 75 Hz
Pixel Pitch	0.297mm x 0.297mm
Response Time	2ms (Rise time), 6ms (Decay time) typical
Viewable Image Size	Horizontal: 12.02" / 305.3 mm Vertical: 9.02" / 229.1 mm
Backlight	2 CCFL backlight bulbs
Video Input Connectors	Analog (VGA / HD-15), Digital (DVI-D)
Viewing Angle	140° / 125° (H / V) - <i>(Viewing angle of LCD panel sans touch)</i>
Contrast Ratio	500:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Operating Temperature	0 - 45C (32 to 113 F) Humidity 20% ~ 85%, non-condensing
Storage Temperature	-20 - 60C (-4 to 140 F) Humidity 10% to 90%, non-condensing
Input	12VDC input at LCD, Rear mounted AC power supply included, 100 – 240VAC (removable)
Power Consumption	Power Consumption: <40W (typical)
Backlighting Life	40,000 Hr Typical
Control Buttons	Rear mounted
Environmental	NEMA 4 / IP65 Front Panel protection against windblown dust and rain, splashing water, and hose-directed water

Panel Finish	Black Baked Enamel
--------------	--------------------

Available Rack Mount Models:
- Designed to fit standard 19" EIA Racks

- SV-1500T2-RM-RT**
- Resistive Touch with Serial/DB9 and USB Interface
- SV-1500T2-RM-CT-SERIAL**
- Capacitive Touch with Serial/DB9 Interface
- SV-1500T2-RM-CT-USB**
- Capacitive Touch Screen with USB interface

Dimensions	Rack Mount: 19.0"(W) x 12.22"(H) x 3.19"(D)* 482.6mm x 310.38mm x 81.0mm* (* remove 1.26" or 32mm from Depth for Removable Power Supply)
------------	--

Additional Options	<ul style="list-style-type: none"> - Custom painted bezel designs available - ODM/OEM to meet exact needs, call to discuss your needs - Removable Computer Module on LCD Monitor
--------------------	---

Product Bundle	Bundle with a Stealth LittlePC or Rackmount Computer and Save - see <i>pricelist links above for more details</i>
----------------	--

Warranty	2 Year Parts & Labor
----------	----------------------

NOTE: Specifications subject to change without notice.