



**Features:**

- Panel Mount LCD, 17" Industrial Grade
- NEMA 4/IP56 Environmentally Sealed
- Touch Screen Options (Resistive or Capacitive)
- Wide Viewing Angles
- 300 Nits of Brightness, Adjustable Controls
- Stainless Steel & Custom painted bezel options
- 2 Year Warranty
- Also available in Rackmount and OEM/Open-Frame Designs

**SV-1700P-PM - Pricelist**

## 17" Panel Mount LCD Monitor

Stealth builds high quality LCD monitors suited for industrial and commercial applications. Our 17" Panel Mount LCD comes equipped with an environmentally sealed front panel that is resistant to splashes or hose downs. All Stealth Panel Mount LCD products are easily installed by securing the rear studs into your console, panel or wall.

We offer Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 6.4" up to 24" diagonal sizes. Stealth's LCD products are environmentally sealed to NEMA 4, 4X, 12, IP52, IP56 and are ideal for applications where dirt, dust, moisture and water are present. Stealth Computers rugged LCD products are constructed from solid steel and stainless steel for corrosion resistance applications. Our LCDs are available with various Touch Screen options including Resistive or Capacitive. For non-touch applications our anti-glare protective glass overlay is installed for maximum protection.

Stealth is an ISO 9001 manufacturer with two decades of proven success at delivering high quality product solutions and excellent support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584).

### SV-1700P-PM Specifications

Screen Size	17.0" (Diagonal)
-------------	------------------

Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Horizontal Frequency	30 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 76 Hz
Pixel Pitch	0.294mm x 0.294mm
Response Time	5ms Typical
Type	TFT Active Matrix Liquid Crystal
Video Input	VGA / HD15 and DVI-D
Viewing Angle	85 (up), 85 (down), 85 (left), 85 (right) - ( <i>Viewing angle of LCD panel sans touch/AR glass</i> )
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	300 cd/m2 typical at center (300 Nits)
Viewable Image Size	Horizontal: 13.3" / 337.9 mm Vertical: 10.6" / 270.4 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync, Composite Sync, Sync on Green, (Positive/Negative)
Operating Temperature	0 - 40C (32 to 104 F) Humidity 30% ~ 80%, non-condensing Altitude Sea Level to 12,000 ft
Storage Temperature	-10 - 60C (-14 to 140 F) Humidity 10% to 90%, non-condensing Altitude Sea Level to 53,000 ft.
Input	AC Input: 100-240 V ~ 50/60 Hz, 0.7A @ 100-120VAC, 0.36A @ 220-240VAC
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out

Environmental	NEMA 4 / IP56 Front Panel protection against windblown dust and rain, splashing water, and hose-directed water
Panel Finish	Black Baked Enamel
Unit Weight	Unit 25.05 lbs (11.36 Kgs)

Available Panel Mount Models:  
- NEMA 4 / 4X sealed when properly installed

**SV-1700P-PM**  
- *Protective Anti-Reflective Glass*

**SV-1700P-PM-RT**  
- *Resistive Touch with USB and Serial/DB9 Interface*

**SV-1700P-PM-CT**  
- *Capacitive Touch with Serial/DB9 Interface*

**SV-1700P-PM-CT-USB**  
- *Capacitive Touch Screen with USB interface*

Dimensions	<b>Panel Mount:</b> 18.94"(W) x 17.0"(H) x 2.85"(D) 481mm x 431.8mm x 72.4mm
------------	--

Additional Options

- Stainless Steel Panel Mount Bezel
- Custom painted bezel designs available
- ODM/OEM to meet exact needs, call to discuss your needs

Product Bundle	Bundle with a Stealth LittlePC or Panelmount Computer and Save - <i>see pricelist links above for more details</i>
----------------	---

Warranty 2 Year Parts & Labor

*NOTE: Specifications subject to change without notice.*