



**19.0" Sunlight Readable LCD Monitor**

- 1,000 Nits (Cd/m<sup>2</sup>) HIGH BRIGHTNESS
- NEMA 4/4X Sealed Front Panel
- Rugged Stainless Steel construction
- 19.0" TFT Active Display Area
- Touchscreen or Protective Glass
- Remote Brightness Control option
- Custom OEM Designs Available




**StealthVU High Brightness, Sunlight Readable Monitors**

Stealth.com high bright LCD monitors are sunlight readable displays designed to operate in extreme ambient light conditions. Stealth monitors outperform commercially available products that wash out in direct and indirect sunlight conditions.

Ideal for inside and outside use in marine, mobile, kiosks, control, security or digital sign applications.

Stealth.com has a wide range of industrial LCD product offerings that include; NEMA 4/4X Stainless Steel, Panel Mount, Rackmount, Open Frame and custom designed configurations.

MODEL SIZE	19"		
BASE MODELS	SV-1900L-HB-PM-SS (Panel Mount, Stainless) SV-1900L-OEM-HB (OEM, Open Frame design)	Environmental (for Panel Mount)	STANDARD: NEMA 4X Front Panel protection against windblown dust and rain, splashing water, hose-directed water and corrosion
Screen Size	19.0" (Diagonal)	Power Consumption	59W
Type	TFT Active Matrix Liquid Crystal	Controls Rear	Power Switch, Menu Key, Select (+, -), Auto
Brightness	1000 cd/m <sup>2</sup> (nits) (adjustable)	Controls On-Screen Display	Brightness, Contrast, H/V Position, Color, Phase, Clock, Language, etc.
Colors	Analog Input: 16.7 million	Dimensions (W x H x D)	Panel Mount: 21.0"(W) x 17.5"(H) x 2.5"(D)* OEM Chassis - 17.75" (W) x 13.5" (H) x 2.3"(D)* *Add 2" with rear-mounted AC Adapter

<b>Response</b>	5ms (Typical)	<b>Unit Weight</b>	Unit 19 lbs (8.65 Kgs) aprox
<b>Contrast Ratio</b>	800:1	<b>Operating</b>	Temperature 32 to 104° F ( 0 to 40° C ) Humidity 30% ~ 80%, non-condensing
<b>Viewing Angle</b>	Horizontal: 80°/80° Vertical: 80°/80°	<b>Shipping/Storage</b>	Temperature -14° to 140°F (-10 to 60°C) Humidity 10% to 90%, non-condensing
<b>Pixel Pitch</b>	0.297mm (H) x 0.297mm (V)	<b>Panel Finish</b>	Stainless Steel (brushed) Panel Mount
<b>Resolutions Supported</b>	Auto Sync. from 640 x 480, 800 x 600, 1024 x 768, to 1280 x 1024	<b>Warranty</b>	1 Year Parts & Labor
<b>Native Mode</b>	1280 x 1024 (SXGA)	<b>Options</b>	<ul style="list-style-type: none"> <li>• Remote Brightness Adjustment (external potentiometer)</li> <li>• OEM Custom Designs</li> <li>• Custom Paint</li> </ul>
<b>Video Signal</b>	RGB Analog 0.7V P/P		
<b>Sync Signal</b>	Separate sync: TTL level (Positive/Negative)		
<b>Signal Cables</b>	6 ft, 15pin D-sub cable, included DVI-D cable extra		
<b>Connector Type</b>	Analog 15 Pin D-Sub & Digital DVI-D		
<b>Viewable Image Size</b>	Horizontal: 14.82" / 376.32 mm Vertical: 11.85" / 301.06 mm		
<b>Power Input</b>	12VDC Power Input 		
<b>Power Supply</b>	External 65 W Adapter 100-240VAC, 47-63Hz (12VDC @ 5.4A)		
<b>Protective Shield</b>	Anti-Reflective Protective Glass Overlay		
<b>Touchscreen (optional)</b>	RESISTIVE or CAPACITIVE		
	<i>NOTE: Specifications subject to change without notice.</i>		



*(Image shown: NEMA 4X Panel Mount with Stainless Steel Bezel)*