

- Wide Viewing Angles
- 250 Nits of Brightness, Adjustable Controls
- Stainless Steel & Custom painted bezel options
- 2 Year Warranty
- Also available in Panelmount and OEM/Open-Frame Designs

SV-1900PL-RM -

Pricelist

Side View

Rear Controls/ Connectors

19" Rack Mount LCD Monitor

Stealth builds high quality LCD monitors suited for industrial and commercial applications. The model SV-1900PL-RM is our 19" Rack Mount LCD is easily installed into industry standard 19" EIA rack cabinets and enclosures in minutes. Our rack mountable LCD products are built with an environmentally sealed NEMA 4, 4X, 12, IP65 front panel that is resistant to dust/dirt penetration or even liquid splashes. All of our LCDs are available with various Touch Screen options including Resistive or Capacitive. For non-touch applications our anti-glare protective glass overlay is installed for maximum protection.

Stealth offers a range of LCD product offerings including Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 6.5" up to 26" diagonal sizes. Our LCD products are constructed from solid steel and will meet the demands of your application without breaking your budget.

An ISO 9001 manufacturer with over two decades of proven success, Stealth has built a reputation for delivering quality solutions and support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584).







Front View



Rear View



## SV-1900PL-RM Specifications

Screen Size	19.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Horizontal Frequency	30 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.294mm x 0.294mm
Response Time	5ms Typical
Туре	LCD c/w LED Backlighting
Viewable Image Size	Horizontal: 14.81" / 376.32 mm Vertical: 11.85" / 301.06 mm
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel sans touch/AR glass)
Contrast Ratio	1000:1 (typical) SmartContrast: 20,000,000:1
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Video Input Connectors	Analog (VGA / HD-15), DVI Compliant Digital HDCP (DVI-D)
Sync Signal	Separate Sync, Sync on Green, (Positive/Negative)
Operating Temperature	0 - 40C (32 to 104 F) Humidity 20% ~ 80%, non-condensing
Storage Temperature	-20 - 60C (-4 to 140 F) Humidity 20% to 80%, non-condensing
Input	AC Input: 100-240VAC 60/50 Hz @ 0.7A
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM

	Lockout, OSM Time-out
Environmental	NEMA 4 / IP65 Front Panel protection against windblown dust and rain, splashing water, and hose-directed water
Panel Finish	Black Baked Enamel
Unit Weight	17 Pounds (7.711Kg)
Available Rack Mount Models: - Designed to fit standard 19" EIA Racks	<b>SV-1900PL-RM-RT</b> - Resistive Touch with Serial/DB9 and USB Interface <b>SV-1900PL-RM-CT-SERIAL</b> - Capacitive Touch with Serial/DB9 Interface <b>SV-1900PL-RM-CT-USB</b> - Capacitive Touch Screen with USB interface
Dimensions	<b>Rack Mount:</b> 19.0"(W) x 15.75"(H) x 2.56"(D) 482.6mm x 400mm x 65mm
Additional Options	<ul> <li>Custom painted bezel designs available</li> <li>ODM/OEM to meet exact needs, call to discuss your needs</li> <li>Removable Computer Module on LCD Monitor</li> </ul>
Product Bundle	Bundle with a Stealth LittlePC or Rackmount Computer and Save - see pricelist links above for more details
Warranty	2 Year Parts & Labor

NOTE: Specifications subject to change without notice.