

Model: FR-2001-17-KVM-Cat6 - Datasheet



Features:

- **Cat6 KVM with 8, 16 and 32 Ports**
- RJ45 Interface with USB or PS/2 Dongles
- 19" Slim 1U Rack LCD / Keyboard/ Mouse
- Control multiple systems from one LCD up to 120 ft or 40m away
- 8/16/32 Keyboard/Video/Mouse Inputs
- Easily Installs into 19" Rack Cabinets
- Folds down to 2U, 3.5" high
- Field selectable for USB and PS/2
- Built-in lockable Slide Rails
- Optional DC Power, Screen Sizes, Video Inputs



Close up of the Rear View of Cat-6 KVM showing Qty 8 RJ45 interface Ports



Close up of the Rear View of Cat-6 KVM showing Qty 16 RJ45 interface Ports



Close up of the Rear View of Cat-6 KVM showing Qty 32 RJ45 interface Ports

FR-2001-17-KVM-Cat6 - Pricelist

17" FlatRack LCD/Keyboard 2U Rack Drawer w/ 8, 16 & 32 Port Cat6 KVM

Manage your Rack Space with a Slim 2U All-In-One LCD/Keyboard with 8, 16 or 32 Built-in Cat6 KVM Ports with Standard RJ45 Interface Connection

The Stealth 8, 16 and 32 Port KVM series FlatRacks present an uncomplicated way for you to manage and

expand your data center efficiently. PS/2 or USB combined with VGA or DVI connections are simply plugged into a small dongle that interfaces to a CAT5/CAT6 (RJ45 Connectors) cable. This allows each installation to a host system (Computer or Server) a maximum distance of up to 120 feet or 40 meters.

Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 1.75 inches or 1U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

Stealth.Com is an ISO 9001 manufacturer with over two decades of delivering quality solutions and support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584) or International 905-264-9000.

FR-2001-17-KVM-Cat6 Specifications

Construction & Design	19" Rackmount steel chassis 2U , 3.5" or 88.9mm high
Screen Size	17.0" (Diagonal)
Type	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Response Time	1.3ms Typical
Viewable Image Size	Horizontal: 13.3" / 338 mm Vertical: 10.6" / 270 mm
Video Input	VGA / HD15 (Standard) DVI-D (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Built-in Controls for Brightness, Size, Contrast, H-V Position, Frequency, etc.

Inputs	Video: ANALOG: 0.7Vp-p Keyboard/Touchpad: PS/2 and USB Combo cables included
Power (VAC/VDC)	External 100~240VAC, 50/60Hz Adapter 12VDC Input @5A
Power Consumption	Max. 48 Watts, Standby 5 Watts
Keyboard	104 Keys
Mouse Touch Pad	3 Button Glide Point
Security	Latching front panel w/ 2-point lock
Operating Temperature	0 - 50C (32 to 122 F)
Storage Temperature	-5 - 60C (-23 to 140 F)
Humidity	5~90%, non-condensing
Shock	10G acceleration (11ms duration)
Vibration	5~500Hz 1G RMS random vibration
Color	Black (standard)
Unit Weight	Unit 37 lbs.(17.0 kgs.)

FR-2001-17-KVM8-Cat6

- 17" LCD/Keyboard/Trackpad with 8-Port Cat6 KVM

FR-2001-17-KVM16-Cat6

- 17" LCD/Keyboard/Trackpad with 16-Port Cat6 KVM

FR-2001-17-KVM32-Cat6

- 17" LCD/Keyboard/Trackpad with 32-Port Cat6 KVM

Available Models:

Dimensions	19.0"(W) x 3.5"(H) x 18.9"(D) (482.6 x 89.0 x 480 mm)
------------	--

Additional Options

- KVM version with 8 or 16 inputs available
- Resistive/Capacitive Touchscreen
- 12/24/48VDC Power supply

- DVI-D, BNC, S-Video, RCA Inputs

Product Bundle

Bundle with a Stealth Rackmount Computer and Save
- *see pricelist links above for more details*

Warranty

2 Year Parts & Labor

NOTE: Specifications subject to change without notice.