







Close up of the Rear View of KVM Rack showing Qty 16 Video / Kybd / Mouse Ports (FR-1001 model ports shown)

Model: FR-2001-17-KVM - Datasheet

Features:

- KVM with 8 or 16 Ports (DB-15)
- 17" Slim 2U Rack LCD / Keyboard / Mouse
- Saves Expensive Rack Space!
- Easily Installs into 19"
 Rack Cabinets
- Folds down to 2U, 3.5" high
- Built-in Keyboard & Touchpad Mouse
- Field selectable for USB and PS/2
- 17.0" Bright Active Display Area
- Built-in lockable Slide Rails
- Optional DC Power, Screen Sizes, Video Inputs

FR-2001-17-KVM -Pricelist

17" LCD Monitor / Keyboard & Trackpad 2U Rack Drawer with 8 & 16 Port KVM

Manage your Rack Space with a Slim 2U All-In-One LCD/Keyboard & Mouse with 8 or 16 Built-in KVM Ports

Manage and expand your data center cost efficiently with the Stealth 8 and 16 Port KVM series FlatRacks. Stealth's LCD products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 3.5 inches or 2U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, and various video inputs.

Stealth.Com is an ISO 9001 manufacturer with over two decades of delivering quality solutions and support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises

right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584) or International 905-264-9000.

FR-2001-17-KVM Specifications

Construction & Design	19" Rackmount steel chassis 2U , 3.5" or 88.9mm high
Screen Size	17.0" (Diagonal)
Туре	TFT Active Matrix Liquid Crystal
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Response Time	1.3ms Typical
Viewable Image Size	Horizontal: 13.3" / 338 mm Vertical: 10.6" / 270 mm
Video Input	VGA / HD15 (Standard) DVI-D (Optional)
Viewing Angle	80 (up), 80 (down), 80 (left), 80 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Controls On-Screen Display	Built-in Controls for Brightness, Size, Contrast, H-V Position, Frequency, etc.
Inputs	Video: ANALOG: 0.7Vp-p Keyboard/Touchpad: PS/2 and USB Combo cables included
Power (VAC/VDC)	External 100~240VAC, 50/60Hz Adapter 12VDC Input @5A
Power Consumption	Max. 48 Watts, Standby 5 Watts
Keyboard	104 Keys
Mouse Touch Pad	3 Button Glide Point
Security	Latching front panel w/ 2-point lock

Operating Temperature	0 - 50C (32 to 122 F)	
Storage Temperature	-5 - 60C (-23 to 140 F)	
Humidity	5~90%, non-condensing	
Shock	10G acceleration (11ms duration)	
Vibration	5~500Hz 1G RMS random vibration	
Color	Black (standard)	
Unit Weight	Unit 37 lbs.(17.0 kgs.)	
Available Models:	FR-2001-17-KVM8 - 17" LCD/Keyboard/Trackpad with 8-Port KVM (DB-15) FR-2001-17-KVM16 - 17" LCD/Keyboard/Trackpad with 16-Port KVM (DB-15)	
Dimensions	19.0"(W) x 3.5"(H) x 18.9"(D) (482.6 x 89.0 x 480 mm)	
Additional Options	 KVM (Cat6) version with 8, 16 or 32 inputs available Resistive/Capacitive Touchscreen 12/24/48VDC Power supply DVI-D, BNC, S-Video, RCA Inputs 	
Product Bundle	Bundle with a Stealth Rackmount Computer and Save - see pricelist links above for more details	
Warranty	2 Year Parts & Labor	
NOTE: Specifications subject to change without notice.		