

**Model: FR-2001-19 -
Datasheet**

Features:

- **19" Slim 2U Rack LCD / Keyboard / Mouse**
- Saves Expensive Rack Space!
- Easily Installs into 19" Rack Cabinets
- Folds down to 2U, 3.5" high
- Built-in Keyboard & Touch Pad Mouse
- Field selectable for USB and PS/2
- 19.0" Bright Active Display Area
- Built-in lockable Slide Rails
- Optional 8, 16 & 32 port KVM, DC Power, Screen Sizes, Video Inputs



Front View with Touchpad
Mouse (standard)



Front View with Optional
Trackball Mouse



Rear View
and open

FR-2001-19 - Pricelist

19" LCD Monitor / Keyboard & Touchpad 2U Rack Drawer

Optimize your Rack Space with a 2U All-In-One LCD/Keyboard/Touchpad Mouse in a Drawer

Stealth FlatRack products have been designed for easy installation into standard 19" rack cabinets. The high strength slide-rails have lockable fixed positions to prevent movement when typing. In its resting position the Stealth LCD monitor measure only 3.5 inches or 2U in height providing a significant cost savings by using less rack space.

Stealth's ultra-thin LCD monitors come equipped with built-in keyboard and a track pad mouse connecting to both USB and PS/2 interfaces. Standard units ship with a built-in 110/220VAC power supply. Optional DC Power inputs of +12, +24 and -48VDC are also available. Other FlatRack models are available with a range of LCD sizes, Widescreen, KVM Ports, and various video inputs.

Stealth.Com is an ISO 9001 manufacturer with over two decades of delivering quality solutions and support all over the world. Our proven track record is reflected in our impressive customer list that includes fortune 500's, governments, educational institutions, as well as small and midsize enterprises

right down to sole proprietorships. Contact us today to discuss your application with one of our product specialists. Toll Free: 1-888-STEALTH (1-888-783-2584) or International 905-264-9000.

FR-2001-19 Specifications

Construction & Design	19" Rackmount steel chassis 2U , 3.5" or 88.9mm high
Screen Size	19.0" (Diagonal)
Type	LCD c/w LED Backlighting
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Response Time	5ms Typical
Viewable Image Size	Horizontal: 14.8" / 376 mm Vertical: 11.8" / 301 mm
Video Input	VGA / HD15 (Standard) DVI-D, HDMI (Optional)
Viewing Angle	80 (up), 80 (down), 85 (left), 85 (right)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	250 cd/m ² typical at center (250 Nits)
Controls On-Screen Display	Built-in Controls for Brightness, Size, Contrast, H-V Position, Frequency, etc.
Inputs	Video: ANALOG: 0.7Vp-p Keyboard/Touchpad: PS/2 and USB Combo cables included
Power (VAC/VDC)	Internal 100~240VAC, 50/60Hz Power Supply
Power Consumption	Max. 48 Watts, Standby 5 Watts
Keyboard	104 Keys
Mouse	2 Button Touch Pad (standard) Optional Trackball Mouse
Security	Latching front panel w/ 2-point lock

Operating Temperature	0 - 50C (32 to 122 F)
Storage Temperature	-5 - 60C (-23 to 140 F)
Humidity	5~90%, non-condensing
Shock	10G acceleration (11ms duration)
Vibration	5~500Hz 1G RMS random vibration
Color	Black (standard)
Unit Weight	Unit 37 lbs.(17.0 kgs.)

Available Models: **FR-2001-19**
- *Standard Model*

Dimensions	19.0"(W) x 3.5"(H) x 18.9"(D) (482.6 x 89.0 x 480 mm)
------------	--

Additional Options

- KVM version with 8 or 16 inputs available
- KVM (Cat6) version with 8, 16 or 32 inputs available
- Resistive/Capacitive Touchscreen
- 12/24/48VDC Power supply
- DVI-D, HDMI, BNC, S-Video, RCA Inputs

Product Bundle	Bundle with a Stealth Rackmount Computer and Save - <i>see pricelist links above for more details</i>
----------------	--

Warranty 2 Year Parts & Labor

NOTE: Specifications subject to change without notice.